



Design data

Boiler model - TT200		
Boiler type - STEAM / WET BACK		
Design EN 12953		
Description	Unit	Value
Steam capacity (nominal load):	tn / h	1,0
Steam outlet temperature	°C	+203
Feed water temperature	°C	+104
Design pressure	bar	16,6
Max. working pressure	bar	16,0
Hydro test pressure	bar	27,0
Trip pressure safety valve	bar	16,0
Boiler weight	kg	5756
Volume of water	m ³	3,7

Connection table

Designation	Application	Amount	Diameter (DN), mm	Pressure (PN), bar	Flanges
a	Flue gas exhaust	1	300	0,1	ISO 7005-1:2011
b	Feed water inlet	1	40	16	ISO 7005-1:2011
c	Steam outlet	1	50	16	ISO 7005-1:2011
d	Safety valve	2	32	40	ISO 7005-1:2011
e	Desalting control valve	1	20	16	ISO 7005-1:2011
f	Water drain	1	40	16	ISO 7005-1:2011
g	Sight hole	1	335x435	-	-
h	Sight hole	1	230x330	-	-
i	Gas analyzer	1	G1/2-B	-	-
k	Condensate drain	1	G1-B	-	-
o	Water level indicator	4	20	16	ISO 7005-1:2011
l	Level limiter min	2	G3/4-B	-	-
w	Level limiter max	1	G3/4-B	-	-
p	Level transducer	1	G3/4-B	-	-
m	Conductivity transducer	1	G1-B	-	-
q	Flue gas temperature sensor	1	G1/2-B	-	-
r	Pressure gauge	1	G1/2-B	-	-
s	Pressure limiter	1	G1/2-B	-	-
z	Pressure transducer	1	G1/2-B	-	-
t	Quick shut-off blow down valve	1	40	16	ISO 7005-1:2011
v	Drain air valve	1	25	16	ISO 7005-1:2011

NOTES:

All dimensions are in mm.
 The design of the boiler complies with the General safety requirements
 PED 2014/68/EU Annex I and the standards of the series EN 12953.

This document is property of ENTROPIC, Munich, Germany. Multiplication or information of its contents to the third parties in any form whatsoever is not allowed without a written authorization by the owner.