



Design data

Boiler model - TT200
 Boiler type - STEAM / WET BACK
 Design EN 12953

Description	Unit	Value
Steam capacity (nominal load):	tn / h	3,0
Steam outlet temperature	°C	+175
Feed water temperature	°C	+104
Design pressure	bar	8,3
Max. working pressure	bar	8,0
Hydro test pressure	bar	12,8
Trip pressure safety valve	bar	8,0
Boiler weight	kg	6340
Volume of water	m ³	7,2

Connection table

Designation	Application	Amount	Diameter (DN), mm	Pressure (PN), bar	Flanges
a	Flue gas exhaust	1	400	0,1	ISO 7005-1:2011
b	Feed water inlet	1	40	16	ISO 7005-1:2011
c	Steam outlet	1	100	16	ISO 7005-1:2011
d	Safety valve	2	32	16	ISO 7005-1:2011
e	Desalting control valve	1	20	16	ISO 7005-1:2011
f	Water drain	1	40	16	ISO 7005-1:2011
g	Sight hole	1	335x435	-	-
h	Sight hole	2	230x330	-	-
i	Gas analyzer	1	G1/2-B	-	-
k	Condensate drain	2	G1-B	-	-
o	Water level indicator	4	20	16	ISO 7005-1:2011
l	Level limiter min	2	G3/4-B	-	-
w	Level limiter max	1	G3/4-B	-	-
p	Level transducer	1	G3/4-B	-	-
m	Conductivity transducer	1	G1-B	-	-
q	Flue gas temperature sensor	1	G1/2-B	-	-
r	Pressure gauge	1	G1/2-B	-	-
s	Pressure limiter	1	G1/2-B	-	-
z	Pressure transducer	1	G1/2-B	-	-
t	Quick shut-off blow down valve	1	40	16	ISO 7005-1:2011
v	Drain air valve	1	25	16	ISO 7005-1:2011

NOTES:

All dimensions are in mm.
 The design of the boiler complies with the General safety requirements PED 2014/68/EU Annex I and the standards of the series EN 12953.

This document is property of ENTROPIC, Munich, Germany. Multiplication or information of its contents to the third parties in any form whatsoever is not allowed without a written authorization by the owner.

Rev	Stage	Main Number	Date	Primary CAD	Date	Project	Nr	Drawing number	Drawing	Bar CODE	Weight (kg)	Scale	1:20	Page
A	Final			Ef.063.000.001 gch		Steam boiler TT200 Evaporation capacity 3 t/h, 8 bar	0000		Boiler		6340	Size A2	01/01	

