



Design data

Boiler model - TT200		
Boiler type - STEAM / WET BACK		
Design EN 12953		
Description	Unit	Value
Steam capacity (nominal load)	tn / h	6,0
Steam outlet temperature	°C	+203
Feed water temperature	°C	+104
Design pressure	bar	16,6
Max. working pressure	bar	16,0
Hydro test pressure	bar	27,0
Trip pressure safety valve	bar	16,0
Boiler weight	kg	17876
Volume of water	m³	12,0

Connection table

Designation	Application	Amount	Diameter (DN), mm	Pressure (PN), bar	Flanges
a	Flue gas exhaust	1	650	0,1	ISO 7005-12011
b	Feed water inlet	1	40	16	ISO 7005-12011
c	Steam outlet	1	125	16	ISO 7005-12011
d	Safety valve	2	40	4,0	ISO 7005-12011
e	Desalting control valve	1	20	16	ISO 7005-12011
f	Water drain	1	40	16	ISO 7005-12011
g	Sight hole	1	335x435	-	-
h	Sight hole	2	230x330	-	-
i	Gas analyzer	1	G1/2-B	-	-
k	Condensate drain	2	G1-B	-	-
o	Water level indicator	4	20	16	ISO 7005-12011
l	Level limiter min	2	G3/4-B	-	-
w	Level limiter max	1	G3/4-B	-	-
p	Level transducer	1	G3/4-B	-	-
m	Conductivity transducer	1	G1-B	-	-
q	Flue gas temperature sensor	1	G1/2-B	-	-
r	Pressure gauge	1	G1/2-B	-	-
s	Pressure limiter	1	G1/2-B	-	-
z	Pressure transducer	1	G1/2-B	-	-
t	Quick shut-off blow down valve	1	40	16	ISO 7005-12011
v	Drain air valve	1	40	16	ISO 7005-12011
x	Air vent	1	20	16	ISO 7005-12011

NOTES:

All dimensions are in mm.
 The design of the boiler complies with the General safety requirements PED 2014/68/EU Annex I and the standards of the series EN 12953.

This document is property of ENTROPIC. No part of this document may be reproduced or transmitted in any form or by any means electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, without written permission by the manufacturer.

Rev.	Stage	Plan Number	Date	Primary CAD	Date	Project	№	Drawing number	Drawing	Bar CODE	Weight (kg)	Scale	1:20	Page	10/11
						Steam boiler TT200	0000		Boiler						

